

# UL2651


## Flat Ribbon Cable 排线

### ■ 产品描述

- 额定温度: 105° C
- 额定电压: 300V
- 导体: 单支或绞合 36~14AWG 镀锡或裸铜
- 绝缘: 聚氯乙烯 (PVC)
- 阻燃等级: VW-1及CSAFT1、FT2
- 参考标准: UL758 UL1581 UL2556
- 适用范围:
- 用于一般电子、电器设备内部连接线

### ■ PRODUCT DESCRIPTION

- Rate temperature: 105° C
- Rate voltage: 300V
- Conductor: 36~14AWG (Solid or stranded, tinned or bare copper)
- Insulation: PVC
- Flame test: VW-1&CSAFT1、FT2
- Reference standard: UL758 UL1581 UL2556
- Application: For internal wiring of electronic and electrical equipment



### ■ 印字 MARKING

无印字 (No printing)

### ■ 产品结构 CABLE CONSTRUCTION



导体 CONDUCTOR					绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20°C, DC)	标准长度 STANDARD PUT-UP	
规格 AWG	间距 Pitch (mm)	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	芯数 (No)	厚度 THICKNESS (mm)	外径 OD (mm)		英制 Ft/Ro11	公制 M/Ro11
28	1.27	7/0.127	0.39	2-64	0.26	0.95	237.25	200	61
26	1.27	7/0.16	0.49	2-64	0.26	1.0	148.94	200	61
24	1.27	11/0.16	0.61	2-64	0.30	1.2	93.25	200	61